

Driveshafts

Front, complete shaft with u-joints FRC8641
 Rear, for Rotoflex rubber coupling TVB000150
 Conversion from rubber Rotoflex to standard u-joint, rear drive shaft, Discovery: for heavy duty use
 Driveshaft FRC8387, Flange Kit STC4858, Spacer 539745, bolts 509045P (x 4), nyloc nuts NZ606041L (x 8)



U-Joints

Defender 110 all RTC3458
 Defender 90, front TVC100010
 Defender 90, rear RTC3458
 Discovery TVC100010
 Rotoflex Coupling Discovery only, with hardware TVF100010G
 Front shaft boot Defender 110 276484
 Defender 90, Disco 276483
 Flange bolts 509045P
 Flange bolt nyloc nuts NZ606041L

2 front, 1 rear (without Rotoflex add 1 more)
 used up to VA541627/VA710668, mid '97
 protects sliding spline

4 per flange (all except Rotoflex)



STC4858

TVF100010G

Differential

complete third member assembly
 Ring & Pinion set 3.54 ratio FTC3620
 4.70 ratio RTC2990
 4.11 ratio front GBR411F
 rear GBR411R

FTC5142 u-joint type, FTC5143 Rotoflex type
 original ratio; includes FTC5413 & FS112301P
 optional ratio for improved power delivery offroad
 optional ratio, critical when running taller tires



NOTE: ON DISCOVERY MODELS EQUIPPED WITH ROTOFLEX DRIVESHAFT YOU MUST REPLACE THE REAR PINION FLANGE AND REAR DRIVESHAFT WHEN FITTING 4:11 or 4:70 GEARS. YOU MUST ALSO REPLACE GEARSETS IN BOTH AXLES.

ARB Air Lockers

Air compressor kit CKMA12
 Differential kit RD128
 Carrier Bearings RTC3095G
 D110 rear RD32
 Optional tire inflation kit PUKT

Air Locker conversion requires one CKMA12 and 1 or 2 RD128
 one per axle, fits front or rear except D110 rear

Salisbury axle, 4.7:1

NOTE: REQUIRES RING GEAR SPACER AND LONGER RING GEAR BOLTS (10 REQ.) WHEN USING 4:70 GEARS

Ring gear spacer RD03A
 Pinion gear nyloc nut NY116041L
 Pinion shims 1.548 MM FTC3853
 sizes up to 1.198MM FTC3867
 Front (outer) pinion bearings 539707G
 Rear (inner) pinion bearings 539706G
 Pinion seal FRC8220
 FTC5258
 Differential carrier side bearings RTC3095G
 Spider (side) gears STC1846
 Spindle (cross shaft) 599945
 Gasket, Diff housing 7316
 Drain plug crush washer 515599

longer bolts req.: 576521
 call with size requirements

up through '97
 '98 on

kit contains 4 gears



CKMA12 Compressor

BP is America's oldest ARB dealer!



RD128 Locking Gear Carrier



FTC5142

GLN001

Wheels and Lug Nuts

Steel Wheels Defender 90 ANR1534PM
 Discovery NTC5193PM
 'Wolf' Wheel, all models ANR4583PM
 Alloy wheel center cap ANR2391MNH
 Lug nut / universal ANR2763MMM
 Lug nut / steel wheels only RRD500010
 Locking lug nuts, alloy wheels GLN001
 Locking lug nuts, steel wheels GLN002

factory steel rim, tough and strong
 with bead lock, great for offroad work

3" diameter
 capped and flared for alloy and steel wheels

Steel rims are commonly used on Defender and Discovery for fitting off road, mud, or snow tires: ours are OEM.



Aluminum 1" Wheel spacers TF301



ANR1534PM



ANR4583PM



ANR2391MNH