

**Driveshafts**

Front, complete shaft with u-joints FRC8641  
 Rear, for Rotoflex rubber coupling TVB000150  
 Conversion from rubber Rotoflex to standard u-joint, rear drive shaft, Discovery: for heavy duty use  
 Driveshaft FRC8387, Flange Kit STC4858, Spacer 539745, bolts 509045P (x 4), nyloc nuts NZ606041L (x 8)



**U-Joints**

Defender 110 all RTC3458  
 Defender 90, front TVC100010  
 Defender 90, rear RTC3458  
 Discovery TVC100010  
 Rotoflex Coupling Discovery only, with hardware TVF100010G  
 Front shaft boot Defender 110 276484  
 Defender 90, Disco 276483  
 Flange bolts 509045P  
 Flange bolt nyloc nuts NZ606041L

2 front, 1 rear (without Rotoflex add 1 more)  
 used up to VA541627/VA710668, mid '97  
 protects sliding spline

4 per flange (all except Rotoflex)



**STC4858**

**TVF100010G**

**Differential**

complete third member assembly  
 Ring & Pinion set 3.54 ratio FTC3620  
 4.70 ratio RTC2990  
 4.11 ratio front GBR411F  
 rear GBR411R

FTC5142 u-joint type, FTC5143 Rotoflex type  
 original ratio; includes FTC5413 & FS112301P  
 optional ratio for improved power delivery offroad  
 optional ratio, critical when running taller tires



**NOTE: ON DISCOVERY MODELS EQUIPPED WITH ROTOFLEX DRIVESHAFT YOU MUST REPLACE THE REAR PINION FLANGE AND REAR DRIVESHAFT WHEN FITTING 4:11 or 4:70 GEARS. YOU MUST ALSO REPLACE GEARSETS IN BOTH AXLES.**

**ARB Air Lockers**

Air compressor kit CKMA12  
 Differential kit RD128  
 Carrier Bearings RTC3095G  
 D110 rear RD32  
 Optional tire inflation kit PUKT

Air Locker conversion requires one CKMA12 and 1 or 2 RD128  
 one per axle, fits front or rear except D110 rear

Salisbury axle, 4.7:1

**NOTE: REQUIRES RING GEAR SPACER AND LONGER RING GEAR BOLTS (10 REQ.) WHEN USING 4:70 GEARS**

Ring gear spacer RD03A  
 Pinion gear nyloc nut NY116041L  
 Pinion shims 1.548 MM FTC3853  
 sizes up to 1.198MM FTC3867  
 Front (outer) pinion bearings 539707G  
 Rear (inner) pinion bearings 539706G  
 Pinion seal FRC8220  
 FTC5258  
 Differential carrier side bearings RTC3095G  
 Spider (side) gears STC1846  
 Spindle (cross shaft) 599945  
 Gasket, Diff housing 7316  
 Drain plug crush washer 515599

longer bolts req.: 576521  
 call with size requirements

up through '97  
 '98 on

kit contains 4 gears



**CKMA12 Compressor**

**BP is America's oldest ARB dealer!**



**RD128 Locking Gear Carrier**



**FTC5142**

**GLN001**

**Wheels and Lug Nuts**

Steel Wheels Defender 90 ANR1534PM  
 Discovery NTC5193PM  
 'Wolf' Wheel, all models ANR4583PM  
 Alloy wheel center cap ANR2391MNH  
 Lug nut / universal ANR2763MMM  
 Lug nut / steel wheels only RRD500010  
 Locking lug nuts, alloy wheels GLN001  
 Locking lug nuts, steel wheels GLN002

factory steel rim, tough and strong  
 with bead lock, great for offroad work

3" diameter  
 capped and flared for alloy and steel wheels



**Aluminum 1" Wheel spacers TF301**



**ANR1534PM**



**ANR4583PM**



**ANR2391MNH**